

SAFETY DATA SHEET

1. Identification

Material name: Vulkem® 351
Material: 875712 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco CPG Inc. - U.S. Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 3

Health Hazards

Acute toxicity (Inhalation - dust and mist) Category 4
Serious Eye Damage/Eye Irritation Category 2B
Respiratory sensitizer Category 1
Skin sensitizer Category 1
Carcinogenicity Category 2

Unknown toxicity - Health

Acute toxicity, oral 16.36 %
Acute toxicity, dermal 32.24 %
Acute toxicity, inhalation, vapor 99.9 %
Acute toxicity, inhalation, dust or mist 99.3 %

Environmental Hazards

Acute hazards to the aquatic environment Category 3

Unknown toxicity - Environment

| | |
|--|---------|
| Acute hazards to the aquatic environment | 61.56 % |
| Chronic hazards to the aquatic environment | 100 % |

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Flammable liquid and vapor.
Harmful if inhaled.
Causes eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Suspected of causing cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/...] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use... to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

| Chemical Identity | CAS number | Content in percent (%)* |
|-------------------------|------------|-------------------------|
| Xylene | 1330-20-7 | 10 - <25% |
| Talc | 14807-96-6 | 10 - <20% |
| Titanium dioxide | 13463-67-7 | 10 - <20% |
| Ethylbenzene | 100-41-4 | 5 - <10% |
| Amorphous silica | 7631-86-9 | 1 - <5% |
| Aluminum oxide | 1344-28-1 | 0 - <1% |
| Dibutyl tin dilaurate | 77-58-7 | 0.1 - <1% |
| Dolomite | 16389-88-1 | 0.1 - <1% |
| Magnesite | 546-93-0 | 0.1 - <1% |
| Isophorone Diisocyanate | 4098-71-9 | 0.1 - <1% |

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact: Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| Chemical Identity | Type | Exposure Limit Values | Source |
|-------------------|---------|-----------------------|--|
| Xylene | STEL | 150 ppm 655 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | REL | 100 ppm 435 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | STEL | 150 ppm 655 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | REL | 100 ppm 435 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | STEL | 150 ppm 655 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | REL | 100 ppm 435 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | STEL | 150 ppm 655 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 100 ppm 435 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 100 ppm 435 mg/m3 | US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008) |
| | STEL | 150 ppm 655 mg/m3 | US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008) |
| | ST ESL | 350 µg/m3 | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | ST ESL | 80 ppb | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | AN ESL | 42 ppb | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | AN ESL | 180 µg/m3 | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | STEL | 150 ppm 655 mg/m3 | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |
| | Ceiling | 300 ppm | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |

| | | | |
|---|---------|---|--|
| | TWA PEL | 100 ppm 435 mg/m3 | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |
| | TWA | 100 ppm | US. ACGIH Threshold Limit Values (2011) |
| | STEL | 150 ppm | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 100 ppm 435 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Talc - Respirable fraction. | TWA | 2 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Talc | TWA | 20 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Talc - Respirable. | TWA | 2.4 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| | TWA | 0.1 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Titanium dioxide | TWA | 10 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Titanium dioxide - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Titanium dioxide - Respirable fraction. | TWA | 15 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Titanium dioxide - Total dust. | TWA | 15 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Titanium dioxide - Respirable fraction. | TWA | 5 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Titanium dioxide - Total dust. | TWA | 50 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Ethylbenzene | TWA | 20 ppm | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 100 ppm 435 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Amorphous silica | TWA | 20 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| | TWA | 0.8 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Aluminum oxide - Respirable fraction. | TWA | 1 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Aluminum oxide - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | TWA | 50 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Aluminum oxide - Respirable fraction. | TWA | 15 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| | TWA | 5 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Aluminum oxide - Total dust. | TWA | 15 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Dibutyl tin dilaurate - as Sn | STEL | 0.2 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| | TWA | 0.1 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 0.1 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Dolomite - Inhalable particles. | TWA | 10 mg/m3 | US. ACGIH Threshold Limit Values (03 2016) |
| Dolomite - Respirable | TWA | 3 mg/m3 | US. ACGIH Threshold Limit Values (03 2016) |

| | | | |
|----------------------------------|-----|--|---|
| particles. | | | |
| Dolomite - Respirable fraction. | TWA | 15 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Dolomite - Total dust. | TWA | 50 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| | TWA | 15 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Dolomite - Respirable fraction. | TWA | 5 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Magnesite - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Magnesite - Respirable fraction. | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Isophorone Diisocyanate | TWA | 0.005 ppm | US. ACGIH Threshold Limit Values (2011) |

| Chemical name | Type | Exposure Limit Values | Source |
|---------------|------|-----------------------|---|
| Xylene | TWA | 100 ppm 434 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009) |
| | STEL | 150 ppm 651 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009) |
| Xylene | TWA | 100 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | STEL | 150 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Xylene | TWA | 100 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | STEL | 150 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Xylene | STEL | 150 ppm 651 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | TWA | 100 ppm 434 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |

| | | | |
|---|---------|-----------------------|---|
| Talc - Respirable. | TWA | 2 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Talc - Respirable dust. | TWA | 3 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Talc | TWA | 2 Fibers/cc | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017) |
| Talc - Respirable fraction. | TWA | 2 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017) |
| Titanium dioxide - Total dust. | TWA | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Titanium dioxide - Respirable fraction. | TWA | 3 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Titanium dioxide | TWA | 10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Titanium dioxide - Total dust. | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Ethylbenzene | TWA | 20 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011) |
| Ethylbenzene | TWA | 20 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Ethylbenzene | STEL | 125 ppm 543 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | TWA | 100 ppm 434 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Amorphous silica - Total | TWA | 4 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Amorphous silica - Respirable. | TWA | 1.5 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Amorphous silica - Respirable dust. | TWA | 6 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Isophorone Diisocyanate | TWA | 0.005 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | CEILING | 0.01 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Isophorone Diisocyanate | TWA | 0.005 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| | CEV | 0.02 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Isophorone Diisocyanate | TWA | 0.005 ppm 0.045 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |

| Chemical name | Type | Exposure Limit Values | Source |
|---|------|-----------------------|---|
| Xylene | TWA | 100 ppm 434 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009) |
| | STEL | 150 ppm 651 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009) |
| Xylene | TWA | 100 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | STEL | 150 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Xylene | TWA | 100 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | STEL | 150 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Xylene | STEL | 150 ppm 651 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | TWA | 100 ppm 434 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Talc - Respirable. | TWA | 2 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Talc - Respirable dust. | TWA | 3 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Talc | TWA | 2 Fibers/cc | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017) |
| Talc - Respirable fraction. | TWA | 2 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017) |
| Titanium dioxide - Total dust. | TWA | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Titanium dioxide - Respirable fraction. | TWA | 3 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Titanium dioxide | TWA | 10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Titanium dioxide - Total dust. | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Ethylbenzene | TWA | 20 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011) |
| Ethylbenzene | TWA | 20 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Ethylbenzene | STEL | 125 ppm 543 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | TWA | 100 ppm 434 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |

| | | | |
|---------------------------------------|------|-----------|---|
| Amorphous silica - Total | TWA | 4 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Amorphous silica - Respirable. | TWA | 1.5 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Amorphous silica - Respirable dust. | TWA | 6 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Aluminum oxide - Respirable. | TWA | 1 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Aluminum oxide - Total dust. | TWA | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| Aluminum oxide - Respirable fraction. | TWA | 3 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| Aluminum oxide - Respirable fraction. | TWA | 1 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Aluminum oxide - Inhalable fraction. | TWA | 10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Aluminum oxide - Respirable fraction. | TWA | 3 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Aluminum oxide - Total dust. - as Al | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Dibutyl tin dilaurate - as Sn | STEL | 0.2 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 0.1 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Dibutyl tin dilaurate - as Sn | TWA | 0.1 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Dibutyl tin dilaurate - as Sn | STEL | 0.2 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | TWA | 0.1 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |

| | | | |
|---|---------|-----------------------|---|
| Dolomite - Respirable fraction. | TWA | 3 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| Dolomite - Total dust. | TWA | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| Dolomite - Respirable fraction. | TWA | 3 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Dolomite - Inhalable fraction. | TWA | 10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Dolomite - Total dust. | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Magnesite - Total dust. | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Isophorone Diisocyanate | TWA | 0.005 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | CEILING | 0.01 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Isophorone Diisocyanate | TWA | 0.005 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| | CEV | 0.02 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Isophorone Diisocyanate | TWA | 0.005 ppm 0.045 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Toluene | TWA | 20 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Toluene | TWA | 20 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Toluene | TWA | 50 ppm 188 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor | TWA | 200 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Petroleum distillates | TWA | 525 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor | TWA | 200 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | TWA | 200 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |

| | | | |
|--|------|-------------------|---|
| Carbon Black - Inhalable | TWA | 3 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011) |
| Carbon Black - Inhalable fraction. | TWA | 3 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Carbon Black | TWA | 3.5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Stoddard solvent (Mineral Spirits) | STEL | 580 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 290 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Stoddard solvent (Mineral Spirits) | TWA | 100 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Stoddard solvent (Mineral Spirits) | TWA | 100 ppm 525 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| 2-Ethylhexanoic acid - Vapor and aerosol, inhalable. | TWA | 5 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| 2-Ethylhexanoic acid - Inhalable fraction and vapor. | TWA | 5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| 1,3,5-Trimethylbenzene | TWA | 25 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| 1,3,5-Trimethylbenzene | TWA | 25 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| 1,3,5-Trimethylbenzene | TWA | 25 ppm 123 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm 123 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm 123 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Naphthalene | STEL | 15 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 10 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Naphthalene | TWA | 10 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Naphthalene | TWA | 10 ppm 52 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | STEL | 15 ppm 79 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |

| | | | |
|---|------|------------------|---|
| Benzene | STEL | 2.5 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 0.5 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Benzene | TWA | 0.5 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| | STEL | 2.5 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Benzene | TWA | 1 ppm 3 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | STEL | 5 ppm 15.5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Chromium | TWA | 0.5 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Chromium - as Cr | TWA | 0.5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Chromium | TWA | 0.5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Nickel | TWA | 0.05 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| Nickel - Inhalable fraction. - as Ni | TWA | 1 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Nickel | TWA | 1 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Cobalt - as Co | TWA | 0.02 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Cobalt - as Co | TWA | 0.02 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Cobalt - as Co | TWA | 0.02 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Arsenic - as As | TWA | 0.01 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Arsenic - as As | TWA | 0.01 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| | STEL | 0.05 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Arsenic - as As | TWA | 0.1 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Beryllium - as Be | TWA | 0.00015 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Beryllium - Inhalable - as Be | TWA | 0.00005 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2017) |
| Beryllium - Inhalable fraction. - as Be | TWA | 0.00005 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017) |

Biological Limit Values

| Chemical Identity | Exposure Limit Values | Source |
|---|--------------------------------|---------------------|
| Xylene (Methylhippuric acids: Sampling time: End of shift.) | 1.5 g/g (Creatinine in urine) | ACGIH BEI (03 2013) |
| Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.) | 0.15 g/g (Creatinine in urine) | ACGIH BEI (02 2014) |

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:

Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection:

Wear goggles/face shield.

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures:

Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:

liquid

Form:

liquid

Color:

Gray

Odor:

Mild petroleum/solvent

Odor threshold:

No data available.

pH:

No data available.

| | |
|--|---|
| Melting point/freezing point: | No data available. |
| Initial boiling point and boiling range: | 121 °C 250 °F |
| Flash Point: | 27 °C 80 °F (Setaflash Closed Cup) |
| Evaporation rate: | Slower than Ether |
| Flammability (solid, gas): | No |
| Upper/lower limit on flammability or explosive limits | |
| Flammability limit - upper (%): | No data available. |
| Flammability limit - lower (%): | No data available. |
| Explosive limit - upper (%): | No data available. |
| Explosive limit - lower (%): | No data available. |
| Vapor pressure: | No data available. |
| Vapor density: | Vapors are heavier than air and may travel along the floor and in the bottom of containers. |
| Relative density: | 1.17 |
| Solubility(ies) | |
| Solubility in water: | Practically Insoluble |
| Solubility (other): | No data available. |
| Partition coefficient (n-octanol/water): | No data available. |
| Auto-ignition temperature: | No data available. |
| Decomposition temperature: | No data available. |
| Viscosity: | No data available. |

10. Stability and reactivity

| | |
|--|---|
| Reactivity: | No data available. |
| Chemical Stability: | Material is stable under normal conditions. |
| Possibility of hazardous reactions: | No data available. |
| Conditions to avoid: | Heat, sparks, flames. |
| Incompatible Materials: | Alcohols. Amines. Strong acids. Strong bases. Water, moisture. |
| Hazardous Decomposition Products: | Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. |

11. Toxicological information

Information on likely routes of exposure

| | |
|----------------------|---|
| Inhalation: | In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes. |
| Skin Contact: | Causes mild skin irritation. May cause an allergic skin reaction. |
| Eye contact: | Causes eye irritation. |

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)****Oral**

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Xylene LD 50 (Rat): 3,523 mg/kg

Titanium dioxide LD 50 (Rat): > 5,000 mg/kg

Ethylbenzene LD 50 (Rat): 3,500 mg/kg

Amorphous silica LD 50 (Rat): > 5,000 mg/kg

Aluminum oxide LD 50 (Rat): > 10,000 mg/kg

Dibutyl tin dilaurate LD 50 (Rat): 2,071 mg/kg

Magnesite LD 50 (Rat): > 2,000 mg/kg

Isophorone Diisocyanate LD 50 (Rat): 4,814 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

| | |
|-------------------------|-------------------------------|
| Xylene | LD 50 (Rabbit): 12,126 mg/kg |
| Ethylbenzene | LD 50 (Rabbit): 17,800 mg/kg |
| Amorphous silica | LD 50 (Rabbit): > 2,000 mg/kg |
| Isophorone Diisocyanate | LD 50 (Rat): > 7,000 mg/kg |

**Inhalation
Product:**

ATEmix: 2.07 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

| | |
|-----------------------|---|
| Xylene | in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study |
| Titanium dioxide | in vivo (Rabbit): Not irritant Experimental result, Supporting study |
| Amorphous silica | in vivo (Rabbit): Not irritant Experimental result, Key study |
| Aluminum oxide | in vivo (Rabbit): Not irritant Experimental result, Key study |
| Dibutyl tin dilaurate | In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study |
| Magnesite | In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Key study |

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

| | |
|------------------|---------------------------------------|
| Xylene | Rabbit, 24 hrs: Moderately irritating |
| Titanium dioxide | Rabbit, 24 hrs: Not irritating |
| Ethylbenzene | Rabbit, 7 d: Slightly irritating |

| | |
|-----------------------|--|
| Amorphous silica | Rabbit, 24 hrs: Not irritating |
| Aluminum oxide | Rabbit, 24 hrs: Not irritating |
| Dibutyl tin dilaurate | Rabbit, 24 hrs: Highly irritating |
| Magnesite | Reconstituted Corneal Epithelium model, 10 min: Not irritating |

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

| | |
|------------------|--|
| Talc | Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans. |
| Titanium dioxide | Overall evaluation: Possibly carcinogenic to humans. |
| Ethylbenzene | Overall evaluation: Possibly carcinogenic to humans. |

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality

Ethylbenzene LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):
Xylene Log Kow: 3.12 - 3.20
Ethylbenzene Log Kow: 3.15
Dibutyl tin dilaurate Log Kow: 3.12

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:
UN1263, PAINT, 3, PG III

CFR / DOT:
UN1263, Paint, 3, PG III

IMDG:
UN1263, PAINT, 3, PG III

Further Information:
The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

| <u>Chemical Identity</u> | <u>OSHA hazard(s)</u> |
|--------------------------|--|
| Benzene | Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye |
| Arsenic | Acute toxicity Skin Liver Cancer Respiratory irritation Nervous system |
| Beryllium | beryllium sensitization skin, eye, and respiratory tract irritation Skin sensitization lung effects (CBD and acute beryllium disease) Cancer |

CERCLA Hazardous Substance List (40 CFR 302.4):

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Xylene | 100 lbs. |
| Ethylbenzene | 1000 lbs. |
| Toluene | 1000 lbs. |
| Naphthalene | 100 lbs. |
| Benzene | 10 lbs. |
| Chromium | 5000 lbs. |
| Nickel | 100 lbs. |
| Arsenic | 1 lbs. |
| Beryllium | 10 lbs. |

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Fire Hazard
- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard
- Flammable (gases, aerosols, liquids, or solids)
- Acute toxicity (any route or exposure)
- Serious eye damage or eye irritation
- Respiratory or Skin Sensitization
- Carcinogenicity
- Hazards Not Otherwise Classified (HNOC)

SARA 302 Extremely Hazardous Substance

| <u>Chemical Identity</u> | <u>Reportable quantity</u> | <u>Threshold Planning Quantity</u> |
|--------------------------|----------------------------|------------------------------------|
| Isophorone Diisocyanate | 500 lbs. | 500 lbs. |

SARA 304 Emergency Release Notification

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Xylene | 100 lbs. |
| Ethylbenzene | 1000 lbs. |
| Isophorone Diisocyanate | |
| Toluene | 1000 lbs. |
| Naphthalene | 100 lbs. |
| Benzene | 10 lbs. |
| Chromium | 5000 lbs. |
| Nickel | 100 lbs. |
| Arsenic | 1 lbs. |
| Beryllium | 10 lbs. |

SARA 311/312 Hazardous Chemical

| <u>Chemical Identity</u> | <u>Threshold Planning Quantity</u> |
|--------------------------|------------------------------------|
| Isophorone Diisocyanate | 500lbs |
| Xylene | 10000 lbs |
| Talc | 10000 lbs |
| Titanium dioxide | 10000 lbs |
| Ethylbenzene | 10000 lbs |
| Amorphous silica | 10000 lbs |
| Aluminum oxide | 10000 lbs |
| Dibutyl tin dilaurate | 10000 lbs |
| Dolomite | 10000 lbs |
| Magnesite | 10000 lbs |

SARA 313 (TRI Reporting)

| <u>Chemical Identity</u> |
|--------------------------|
| Xylene |
| Ethylbenzene |

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Xylene | Reportable quantity: lbs. |

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Xylene
Talc
Titanium dioxide
Ethylbenzene
Amorphous silica

US. Massachusetts RTK - Substance List

Chemical Identity

Xylene
Talc
Titanium dioxide
Ethylbenzene
Amorphous silica
Isophorone Diisocyanate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Xylene
Talc
Titanium dioxide
Ethylbenzene
Amorphous silica

US. Rhode Island RTK

Chemical Identity

Xylene
Talc
Titanium dioxide
Ethylbenzene

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 315 g/l
VOC Method 310 : 26.89 %

Inventory Status:

| | |
|--|--|
| Australia AICS: | One or more components in this product are not listed on or exempt from the Inventory. |
| EINECS, ELINCS or NLP: | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan (ENCS) List: | One or more components in this product are not listed on or exempt from the Inventory. |
| China Inv. Existing Chemical Substances: | One or more components in this product are not listed on or exempt from the Inventory. |
| Korea Existing Chemicals Inv. (KECI): | One or more components in this product are not listed on or exempt from the Inventory. |
| Canada NDSL Inventory: | One or more components in this product are not listed on or exempt from the Inventory. |
| Philippines PICCS: | One or more components in this product are not listed on or exempt from the Inventory. |
| New Zealand Inventory of Chemicals: | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan ISHL Listing: | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan Pharmacopoeia Listing: | One or more components in this product are not listed on or exempt from the Inventory. |
| Canada DSL Inventory List: | All components in this product are listed on or exempt from the Inventory. |
| Ontario Inventory: | One or more components in this product are not listed on or exempt from the Inventory. |
| Mexico INSQ: | One or more components in this product are not listed on or exempt from the Inventory. |
| Taiwan Chemical Substance Inventory: | One or more components in this product are not listed on or exempt from the Inventory. |
| US TSCA Inventory: | All components in this product are listed on or exempt from the Inventory. |

| |
|--|
| 16. Other information, including date of preparation or last revision |
|--|

Revision Date: 03/08/2019

Version #: 1.2

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.