



Dymonic 100 at 40 wet mils



(Recommended, but not required)



**NOTES:**

- Slope to the exterior 1/8" per 12"
- Flashing must be installed past thermal break

See [securockexoair.com](http://securockexoair.com) for the most up-to-date product information

*This detail is intended for conceptual purposes only. Must be reviewed by a project/design professional*

*The following trademarks used herein are owned by USG Corporation or its subsidiaries: SECUROCK, USG, USG in stylized letters. The following trademarks used herein are owned by Tremco Incorporated or its subsidiaries: Tremco, ExoAir, Spectrem, Dymonic, Proglaze, Vulkem.*



**United States Gypsum Company**  
 550 West Adams Street  
 Chicago, IL 60661  
 USG Technical & Customer Support:  
 800.USG.4YOU (874-4968)

**Tremco Commercial Sealants & Waterproofing**  
 3735 Green Road  
 Beachwood, OH 44122  
 Tremco Technical Support:  
 866.209.2404

**SECUROCK® ExoAir® 430 Panel**  
 Project:  
 Detail: Rough Opening - Dymonic 100 - Panel  
 Drawn by: **KAB**    Approved by: **DM**    Scale: NTS

File Name:  
**14135**  
 Date: 3/20/2017

Rev #  
**00**