



# TECHNICAL DATA SHEET

Tremco® 2560  
Asphalt Protection Board 1/4"

---

## PRODUCT DESCRIPTION

Tremco® 2550 Protection Board is a semi-flexible asphaltic sheet. It consists of a core made from a blend of asphalt, plasticizer, and inert fillers. This core is sandwiched between two skins of and asphalt-saturated fiberglass. This composition is then molded and formed under heat and pressure into sheets.

---

## BASIC USES

Tremco 2550 provides protection for approved waterproofing membranes during and after construction. The tough, durable properties of the product make it ideally suited to withstand the shock and impact of rugged backfilling operations, as well as on-site foot traffic. It is used as a protective course for foundation walls, roof terraces, planters, and tunnels.

---

## PACKAGING

1/4" thick, 4' x 8', 40/pallet

---

## LIMITATIONS

- Not for use with Tremco TREMproof® 201/60 or Tremco TREMproof 250GC cold fluid-applied waterproofing membranes.

---

## WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

## TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD
Puncture Resistance at 94 °F	200 min
Indentation	Less than 0.9 mm
Density (lb/ft <sup>2</sup> )	92 lb/ft <sup>2</sup>
Weight (lb/ft <sup>2</sup> )	1.93
Bitumen Content, % by weight	0.45
Inert Residual, % by weight	0.55
Binders, Fiberglass (both sides)	Full width inorganic nonwoven matting
Binders, % inorganic	100%
Bitumen Softening Point °C	108 °C
Anti-Stick Material	Polyethylene Film
Alkali Attack	No Disintegration
Binders, Tensile Strength	
Width (lb)	24 lb
Length (lb)	33 lb
Water Absorption, % weight increase (after 8 hours at 60 °C)	0.26%
Water Permeability (after 1 month)	No leakage, swelling, or deterioration

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

**NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.**

T2560DS/1122

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



[tremcosealants.com](http://tremcosealants.com) | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122  
800.321.7906 | [tremcocpg.com](http://tremcocpg.com)