NOTE: REFER TO TREMCO'S PUBLISHED APPLICATION INSTRUCTIONS FOR ACCEPTABLE JOINT SIDE WALL SUBSTRATE CONDITIONS PRIOR TO INSTALLATION EXISTING CMU, TYP. VARIES TREMCO DYMONIC 100 WILLSEAL 600 TREMCO EXOAIR WRAPPED INTO JOINT PRE-COMPRESSED SYSTEM JOINT SEALANT SUPPLIED SIDEWALL ADHESIVE WILLSEAL CLOSED CELL FOAM WITH ENGINEERED PROFILE FIELD APPLIED INJECTED SEALANT **FACTORY APPLIED AND CURED** BAND BOTH SIDES (OPTIONAL) PICK PICK RESISTANT SEALANT RESISTANT SEALANT SUPPLIED design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Willseal and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Willseal and Tremco to ensure you have the most recent version. Willseal Color Coreseal V Detail: Willseal Color Coreseal V at Brick Joint - Plan View File Name: WCCV-WW-02 Drawn by: KAB Checked by: AM/CB Scale: NTS Date: 2/23/2022

www.tremcocpg.com

Willseal Technical Support: 800-274-2813

