
PRODUCT DESCRIPTION

DrainStar Stripdrain is a two part prefabricated drainage system designed to collect and move below grade water while straining out backfill soils and other particles.. DrainStar Stripdrain is an effective replacement for traditional foundation drain tile and gravel systems, and can be applied to waterproofing applications with or without added foundation drainage boards.

BASIC USES

DrainStar Stripdrain can be applied to below grade waterproofing applications with or without foundation drainage boards. However, applications with foundation drainage boards provide additional assurance that the drainage system will remove to maximum amount of water from the soil as quickly as possible.

FEATURES AND BENEFITS

- By combining DrainStar Strip drain with 12 to 24 inches of quality foundation drainage board such as WARM-N-DRI, you'll match the water collection area of a drain tile and gravel system.
- Exceptional ability to hang on the wall and build targeted thickness, spanning below grade foundation wall cracks of up to 1/8 in with a cured thickness of 60 mils.
- Durability with exceptional elongation and crack-bridging characteristics.

LIMITATIONS

- For applications with foundation drainage boards, the DrainStar Stripdrain should be applied with the dimples facing inward toward the drainage board.
- For applications without foundation drainage board, the dimples should be facing outward.
- Not to be used as an exposed or weathering surface. Limit UV exposure of a maximum of 30 days.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	STRIPDRAIN 6"	STRIPDRAIN 12"
Material	Polypropylene, Needle-Punched Nonwoven	Polypropylene, Needle-Punched Nonwoven
PROPERTY	TEST METHOD	TYPICAL RESULTS
Grab Tensile Strength	ASTM D-4632	115 lbs
Grab Elongation	ASTM D-4632	70%
CBR Puncture Strength	ASTM D-6241	320 lbs
Water Flow Rate	ASTM D-4491	150 gpm/ft ²
Permittivity	ASTM D-4491	2.4 sec ⁻¹
Apparent Opening Size*	ASTM D-4751	70 sieve
UV Resistance	ASTM D-4355	70% / 500 hr

CORE

Material		High Impact Polystyrene	High Impact Polystyrene
Thickness	ASTM D-1777	1 in	1 in
Compressive Strength	ASTM D-1621	6,000 psf	6,000 psf
In-Plane Flow Rate**	ASTM D-4716	21 gpm/ft	21 gpm/ft

*Apparent Opening Size is Maximum Average Roll Value

**In-Plane Flow Rate measured under 3,200 psf (172 kPa) compressive load at hydraulic gradient of 0.1

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

DSWD-DS/0523

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit and Willseal brands; Nudura Inc.; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com