



**NOTES:**

- Minimum 3" overlap required for all dissimilar materials and/or change in plane
- For joints wider than 1" contact your Tremco Technical Services Representative

See [securockexoair.com](http://securockexoair.com) for the most up-to-date product information

*This detail is intended for conceptual purposes only. Must be reviewed by a project/design professional*

*The following trademarks used herein are owned by USG Corporation or its subsidiaries: SECUROCK, USG, USG in stylized letters. The following trademarks used herein are owned by Tremco Incorporated or its subsidiaries: Tremco, ExoAir, Spectrem, Dymonic, Proglaze, Vulkem.*



**PERFORMANCE BUILT IN**  
www.securockexoair.com

**United States Gypsum Company**  
550 West Adams Street  
Chicago, IL 60661

USG Technical & Customer Support:  
800.USG.4YOU (874-4968)

**Tremco Commercial Sealants & Waterproofing**  
3735 Green Road  
Beachwood, OH 44122

Tremco Technical Support:  
866.209.2404

SECUROCK® ExoAir® 430 Panel

Project:  
Detail: **Adjacent Substrates**

Drawn by: **KAB**

Approved by: **DM**

Scale: NTS

File Name:  
**13577**

Rev #  
**00**

Date: **2/7/2017**