



---

### PRODUCT DESCRIPTION

TREMproof® Amphibia™ WS is a hydro-expansive waterstop based on EPDM rubber this is reinforced in the center with a coupled steel mesh that stabilizes and directs the waterstop's expansion.

---

### BASIC USES

TREMproof Amphibia WS is used to seal vertical and horizontal concrete construction joints.

---

### FEATURES AND BENEFITS

- Perfect sealing and high resistance to hydraulic load.
- Excellent dimensional stability even when the volume increases due to premature contact with water.
- Excellent adhesion to the substrate even during casting, adhesion increases as expansion increases in contact with water.
- Quick and easy application by nailing.
- When in contact with water, TREMproof Amphibia WS can increase in volume by up to 5 times while maintaining its density and adapting its shape to the small gaps that are often present in concrete castings.

---

### AVAILABILITY

TREMproof Amphibia WS is immediately available from your local Tremco Sales Representative.

---

### PACKAGING

TREMproof Amphibia WS is available in the following sizes.

- 3/4" x 3/8" x 33' - 3 rolls/case
- 1" x 19/32" x 23' - 3 rolls/case

---

### STORAGE

TREMproof Amphibia WS must be stored in a cool, dry place protected from sun and humidity.

---

### APPLICATION

Below are general application guidelines.

- Even out the fresh concrete along the profile application side with a straight edge or trowel.
- Clean application surface to remove dust and loose material.
- Lay TREMproof Amphibia WS on the application surface with the protective paper facing upwards, then remove it and fasten the profile with the nails provided every 6" (15 cm).
- Butt seal the joints with heat gun, low heat.
- TREMproof Amphibia WS ensures the sealing of construction joints, even when subjected to considerable hydraulic pressure.

---

## LIMITATIONS

- TREMproof Amphibia WS cannot be used as a dilatation joint.
- Must be used on walls that are thick enough to guarantee a minimum cover of 3" (8 cm) on the sides.
- Must be placed on to the application substrate, making sure that no material remains between the TREMproof Amphibia WS and the substrate.
- Spacers or tie rods of the vertical casting must be placed at a minimum distance of 2" to 4" (5 to 10 cm) from the horizontal plane.
- PLEASE NOTE: Contact Tremco Technical Services when applying in the presence of water with a high salt concentration.

---

## WARRANTY

A repair or replacement warranty is available on all Tremco Products. Visit <https://www.tremcosealants.com/warranties/> for details.

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



*Construction Products Group*

3735 Green Rd. | Beachwood, OH 44122  
800.321.7906 | tremcocpg.com