




easydri
CRACK SEAL™

NEAT CONVENIENT EFFECTIVE

Neatly and permanently
seal basement wall leaks.



Finished walls
sealed with
EasyDri.

NEAT:

The two-part EasyDri™ Crack Sealing System is designed to be just as effective in sealing against moisture intrusion as traditional urethane or epoxy crack injections while maintaining the aesthetics of the basement wall. EasyDri gives a smooth, concrete-colored finish with no unsightly ports or oozing sealants.

CONVENIENT:

EasyDri Crack Seal allows for your basement walls to be treated while they are still WET!* Projects can be finished in half the time it takes to complete a conventional crack injection! This system can be used on flat, cement walls as well as basements with brick patterned walls.

EFFECTIVE:

The EasyDri system has the ability to hold back 8 FEET of water under pressure in as little as 8 hours. This provides a complete seal against basement moisture while maintaining a smooth, paintable surface.

*as long as water is not actively flowing through the crack

TREMCO
Barrier Solutions

EASYDRI COATING PROPERTIES

Type	Elastomeric, emulsion based coating
Color	Grey
Application Temperature	45°F (7°C) to 100°F (38°C)
Cure Time	24 hours, dry to touch
Application	Brush / Roll

EASYDRI SEALANT PROPERTIES

Type	Single component polyurethane sealant
Skin Time	2 to 3 hours, ASTM C679
Tack Free Time	6 to 8 hours, 73°F (23°C), 50% RH
% Elongation	800% to 900%, ASTM D412
Application Temperature	45°F (7°C) to 100°F (38°C)



6402 E. Main St., Suite 201 • Reynoldsburg, OH 43068 • 800.876.5624
www.tremcobarriersolutions.com