



Dymonic 100 (Apply to head and 6" down jamb)

Dymonic 100 (Extends minimum 1" on each side of fastener wrapped over the top of screw, terminated at flange to shed water)

**NOTES:**  
- Flashing must be installed past thermal break

See [securockexoair.com](http://securockexoair.com) for the most up-to-date product information

*This detail is intended for conceptual purposes only. Must be reviewed by a project/design professional*

*The following trademarks used herein are owned by USG Corporation or its subsidiaries: SECUROCK, USG, USG in stylized letters. The following trademarks used herein are owned by Tremco Incorporated or its subsidiaries: Tremco, ExoAir, Spectrem, Dymonic, Proglaze, Vulkem.*

 <b>PERFORMANCE BUILT IN</b> <a href="http://www.securockexoair.com">www.securockexoair.com</a>	<b>United States Gypsum Company</b> 550 West Adams Street Chicago, IL 60661  USG Technical & Customer Support: 800.USG.4YOU (874-4968)	<b>Tremco Commercial Sealants &amp; Waterproofing</b> 3735 Green Road Beachwood, OH 44122  Tremco Technical Support: 866.209.2404	<b>SECUROCK® ExoAir® 430 Panel</b> Project: Detail: Nail Flange - ExoAir 110AT - Framing	File Name: <b>15842</b>	Rev # <b>00</b>
			Drawn by: <b>KAB</b>	Approved by: <b>DM</b>	Scale: NTS