



WILLSEAL MODIFIED ACRYLIC
IMPREGNATED MICRO-CELL FOAM

FACTORY APPLIED AND CURED
SILICONE TOPPING

VARIES

FIELD APPLIED EPOXY ADHESIVE
(BOTH SIDES OF JOINT, EPOXY
ADHESIVE SUPPLIED)

FIELD APPLIED SILICONE SEALANT
(BOTH SIDES OF JOINT, SILICONE
SEALANT SUPPLIED)

EXISTING CMU

EXISTING EIFS
EXTERIOR WALL

NOTE: RECESS JOINT $\frac{1}{4}$ " FROM JOINT SURFACE.

The architecture, engineering, and design of the project using the Willseal products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Willseal specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Willseal to ensure you have the most recent version.

Willseal Seismic



Detail: Willseal Seismic at EIFS Corner Joint Application				File Name:
Drawn by: HDE	Checked by: AM	Scale: NTS	Date: 7/7/2022	WS-WW-12
www.tremcocpg.com				

