



COVERAGE RATE CALCULATOR FOR *TREMproof*[®] WATERPROOFING MEMBRANES & *Vulkem*[®] TRAFFIC COATINGS

ENGLISH COVERAGE RATES

Wet Mil Thickness	Square Ft/Gal
215	7.5
165	9.5
150	10
140	11
120	13
95	17
90	18
85	19
80	20
75	21.5
70	23
65	24.5
60	25
55	29
50	32
45	35.5
40	40
35	46
30	53
25	64
20	80
15	107
10	150
8	200
6	267
5	300
4	400
2	800
1	1600

METRIC COVERAGE RATES

Wet Mil Thickness	M3/Litre	M3/US Gal.
5.50	0.19	0.70
4.20	0.23	0.88
3.80	0.25	0.93
3.60	0.27	1.02
3.00	0.32	1.21
2.40	0.42	1.58
2.30	0.44	1.67
2.20	0.47	1.77
2.00	0.49	1.86
1.90	0.53	2.00
1.80	0.57	2.14
1.70	0.60	2.28
1.50	0.66	2.51
1.40	0.71	2.70
1.30	0.79	2.98
1.10	0.87	3.30
1.00	0.98	3.72
0.90	1.13	4.28
0.80	1.30	4.93
0.60	1.57	5.95
0.50	1.97	7.44
0.40	2.63	9.95
0.30	3.69	13.95
0.20	4.92	18.60
0.15	6.57	24.83
0.13	7.38	27.90
0.10	9.84	37.20
0.05	19.68	74.40
0.03	39.27	148.80