

SAFETY DATA SHEET

1. Identification

Material name: TREMPRO CHEM X PRO Gray (15x600 ML SSG) Material: 833GRYT385

Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants 220 Wicksteed Ave Toronto ON M4H 1G7 CA

Contact person: Telephone: Emergency telephone number:

EH&S Department 1-800-263-6046 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Carcinogenicity	Category 2

Unknown toxicity - Health

Acute toxicity, oral	56.04 %
Acute toxicity, dermal	60.13 %
Acute toxicity, inhalation, vapor	99.97 %
Acute toxicity, inhalation, dust or mist	99.55 %

Environmental Hazards

Acute hazards to the aquatic	Category 3
environment	
nown toxicity - Environment	

Unknown toxicity - Environment

Acute hazards to the aquatic	96.78 %
environment	
Chronic hazards to the aquatic	100 %
environment	

Label Elements

Hazard Symbol:



Signal Word:	Warning
Hazard Statement:	Harmful if inhaled. Suspected of causing cancer. Harmful to aquatic life.
Precautionary Statements	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	20 - <50%
Calcium Carbonate (Limestone)	1317-65-3	10 - <20%
Vinyltrimethoxysilane	2768-02-7	1 - <5%
Diisodecyl phthalate	26761-40-0	1 - <5%
3-Aminopropyltrimethoxysilane	13822-56-5	1 - <5%
Titanium dioxide	13463-67-7	1 - <5%
Polypropylene glycol	25322-69-4	0 - <1%
Stearic acid	57-11-4	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures



Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.	
Inhalation:	Move to fresh air.	
Skin Contact:	Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.	
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.	
Most important symptoms/effect	s, acute and delayed	
Symptoms:	May cause skin and eye irritation.	
Indication of immediate medical a	ttention and special treatment needed	
Treatment:	Symptoms may be delayed.	
5. Fire-fighting measures		
General Fire Hazards:	No unusual fire or explosion hazards noted.	
Suitable (and unsuitable) extingu	iishing media	
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.	
Special protective equipment an	d precautions for firefighters	
Special fire fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.	
6. Accidental release measures	S	
Personal precautions, protective equipment and emergency procedures:	No data available.	
Methods and material for containment and cleaning up:	Collect spillage in containers, seal securely and deliver for disposal according to local regulations.	



Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.
7. Handling and storage	
Precautions for safe handling:	Do not taste or swallow. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.
Conditions for safe storage, including any incompatibilities:	Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Stearic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)



Chemical name	Туре	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Vinyltrimethoxysilane	STEL	10 ppm 60 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Stearic acid	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stearic acid	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	
	TWA	0.1 mg/m3	Regulation Respecting the Quality of the Work Environment) (09 2017)
Aluminum oxide - Respirable.	TWA	1 mg/m3	 Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum oxide - Total dust.	TWA	10 mg/m3	 Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	 Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	 Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum oxide - Inhalable fraction.	TWA	10 mg/m3	 Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Total dust. - as Al	TWA	10 mg/m3	 Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Methanol	STEL	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methanol	STEL	250 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm 328 mg/m3	Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	200 ppm 262 mg/m3	 Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)



Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Iron oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Dust as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume as Fe	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Iron oxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Iron oxide - Dust and fume as Fe	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Amorphous silica - Total	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Zirconium dioxide - as Zr	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Zirconium dioxide - as Zr	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zirconium dioxide - as Zr	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Propylene oxide	TWA	2 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Propylene oxide	TWA	2 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Propylene oxide	TWA	20 ppm	48 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Acetaldehyde	CEILING	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Acetaldehyde	CEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Acetaldehyde	CEILING	25 ppm	45 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Appropriate Engineering
ControlsMechanical ventilation or local exhaust ventilation may be required.
Observe good industrial hygiene practices. Observe occupational exposure
limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.	
Eye/face protection:	Wear safety glasses with side shields (or goggles).	
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.	
Other:	Wear suitable protective clothing.	
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.	
Hygiene measures:	Observe good industrial hygiene practices. Do not eat, drink or smoke when using the product. Wash hands after handling. Wash hands before breaks and immediately after handling the product.	

9. Physical and chemical properties



Appearance

Physical state:	solid
Form:	Paste
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explo	sive limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.46
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
10. Stability and reactivity	

10.	Stability	and	reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information



Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	Harmful if swallowed.
Symptoms related to the physica	I, chemical and toxicological characteristics
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.
Information on toxicological effect	cts
Acute toxicity (list all possible	routes of exposure)
Oral Product:	ATEmix: 4,873.08 mg/kg
Dermal Product:	Not classified for acute toxicity based on available data.
Specified substance(s): Calcium carbonate	LD 50 (Rat): > 2,000 mg/kg
Diisodecyl phthalate	LD 50 (Rabbit): > 3,160 mg/kg
Polypropylene glycol	LD 50 (Rabbit): > 2,000 mg/kg
Stearic acid	LD 50 (Rabbit): > 2,000 mg/kg
Inhalation Product:	ATEmix: 2.7 mg/l
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.



Specified substance(s): Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study
Vinyltrimethoxysilane	in vivo (Rabbit): Not irritant Experimental result, Key study
3- Aminopropyltrimethoxy silane	in vivo (Rabbit): Irritating Experimental result, Key study
Titanium dioxide	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Polypropylene glycol	in vivo (Rabbit): Not irritant Experimental result, Key study
Stearic acid	in vivo (Rabbit): Not irritant Experimental result, Key study

Seriou Pro

ous Eye Damage/Eye Irritatio Product: Specified substance(s):		on No data available.	
	Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating	
	Vinyltrimethoxysilane	Rabbit: Not irritating	
	3- Aminopropyltrimethoxy silane	Rabbit, 24 - 72 hrs: Highly irritating	
	Titanium dioxide	Rabbit, 24 hrs: Not irritating	
	Polypropylene glycol	Rabbit, 1 - 48 hrs: Moderately irritating	
	Stearic acid	Rabbit, 27 - 72 hrs: Not irritating	

Respiratory or Skin Sensitization Product: No data available.

Carcinogenicity Product:

Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide Overall evaluation: Possibly carcinogenic to humans.

- US. National Toxicology Program (NTP) Report on Carcinogens: No carcinogenic components identified
- US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified



Germ Cell Mutagenicity

In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Specific Target Organ Toxicity Product:	- Single Exposure No data available.
Specific Target Organ Toxicity Product:	- Repeated Exposure No data available.
Aspiration Hazard Product:	No data available.
Other effects:	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.	
Specified substance(s): Diisodecyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality	
Polypropylene glycol	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): > 10,000 mg/l Mortality	
Aquatic Invertebrates Product:	No data available.	
Specified substance(s): Diisodecyl phthalate	EC 50 (Opossum shrimp (Americamysis bahia), 96 h): > 0.08 mg/l Mortality	
Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication	



Chronic hazards to the aquatic environment:

Fish Product:	No data available.	
Aquatic Invertebrates Product:	No data available.	
Toxicity to Aquatic Plants Product:	No data available.	
Persistence and Degradability		
Biodegradation Product:	No data available.	
BOD/COD Ratio Product:	No data available.	
Bioaccumulative potential Bioconcentration Factor (BCF) Product: No data available.		
Partition Coefficient n-octanol / w Product:	vater (log Kow) No data available.	
Specified substance(s): Stearic acid	Log Kow: 8.23	
Mobility in soil:	No data available.	
Other adverse effects:	Harmful to aquatic organisms.	
13. Disposal considerations		
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.	
Contaminated Packaging:	No data available.	
14. Transport information		

TDG:

Not Regulated



CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	OSHA hazard(s)	
Crystalline Silica	kidney effects	
(Quartz)/ Silica Sand	lung effects	
	immune system effects	
	Cancer	

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methanol	5000 lbs.
Furan	100 lbs.
Propylene oxide	100 lbs.
Acetaldehyde	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Acute toxicity (any route or exposure) Carcinogenicity

SARA 302 Extremely Hazardous Substance

	<u>Reportable</u>	
Chemical Identity	<u>quantity</u>	Threshold Planning Quantity
Furan	100 lbs.	500 lbs.
Propylene oxide	100 lbs.	10000 lbs.



SARA 304 Emergency Release Notification Chemical Identity Reportable quantity

Reportable qua	
5000 lbs.	
100 lbs.	
100 lbs.	
1000 lbs.	

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Furan	500lbs
Propylene oxide	500lbs
Calcium carbonate	10000 lbs
Calcium Carbonate	10000 lbs
(Limestone)	
Vinyltrimethoxysilane	10000 lbs
Diisodecyl phthalate	10000 lbs
3-	10000 lbs
Aminopropyltrimethoxysilane	
Titanium dioxide	10000 lbs
Polypropylene glycol	10000 lbs
Stearic acid	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Chemical Identity	Reportable quantity		
Furan	lbs		
Propylene oxide	lbs		
Acetaldehyde	lbs		

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium carbonate Calcium Carbonate (Limestone) Titanium dioxide



Version: 1.0 Revision Date: 08/01/2018

US. Massachusetts RTK - Substance List

Chemical Identity Calcium carbonate Calcium Carbonate (Limestone) Titanium dioxide Crystalline Silica (Quartz)/ Silica Sand Furan Propylene oxide

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium carbonate Calcium Carbonate (Limestone) Diisodecyl phthalate Titanium dioxide

US. Rhode Island RTK

Chemical Identity

Calcium carbonate Calcium Carbonate (Limestone) Titanium dioxide

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	1 g/l
VOC Method 310	:	0.03 %



Inventory Status: Australia AICS:

Canada DSL Inventory List:All complexempt isEINECS, ELINCS or NLP:One or r
not listedJapan (ENCS) List:One or r
not listedChina Inv. Existing Chemical Substances:One or r
not listedKorea Existing Chemicals Inv. (KECI):One or r
not listedCanada NDSL Inventory:One or r
not listed

Philippines PICCS:

US TSCA Inventory:

New Zealand Inventory of Chemicals:

Japan ISHL Listing:

Japan Pharmacopoeia Listing:

Mexico INSQ:

Ontario Inventory:

Taiwan Chemical Substance Inventory:

One or more components in this product are not listed on or exempt from the Inventory.

All components in this product are listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

All components in this product are listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.



16.Other information, including date of preparation or last revision

Revision Date:	08/01/2018
Version #:	1.0
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.