

Enviro-Dri® Pan & Arch

Cold-applied self-adhering membrane

DATA SHEET

Product Description

Enviro-Dri Pan & Arch is a multi-directionally flexible, cold-applied self-adhering membrane composed of butyl rubber with a creped, cross-laminated polyolefine liner. This product conforms easily and effectively to curved substrates. Because of its unique design, Enviro-Dri Pan & Arch provides an air- and moisture-tight seal and eliminates the need for corner flashing patches. Enviro-Dri Pan & Arch fully integrates with the Enviro-Dri Weather-Resistant Barrier System to provide you with the next level of protection against air and moisture intrusion.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

Features & Benefits

- 75' long roll, with 6" and 8" widths available
- Butyl-based material offering exceptional adhesion to most building materials
- Specifically engineered and designed to provide an air and moisture seal around arched and curved door and window openings
- Flexible design eliminates need for separate corner flashing patches on sides of window openings
- Integrates seamlessly with the Enviro-Dri Field Membrane
- Resists UV degradation for up to 1 year of direct sun exposure
- Provides strong and immediate adhesion over a wide range of installation temperatures, and remains pliable at low temperatures

| TYPICAL MEMBRANE PROPERTIES | | |
|-------------------------------|--|--|
| PROPERTY | DESCRIPTION | |
| COLOR | White | |
| APPLICATION TEMPERATURE RANGE | 20°F - 180°F | |
| PACKAGING | Roll Width: 6" (1 roll/carton) 8" (1 roll/carton) | Roll Length: 75' |
| STORAGE | 8.2 + .15 lbs/gal | Store in an unopened container at between 60°-80°F |
| PROPERTY | TEST METHOD | TYPICAL RESULTS |
| THICKNESS | ASTM D1000 | 50 mils |
| TENSILE STRENGTH (CROSS) | ASTM D412-9 | >400 psi |
| TENSILE STRENGTH (MACHINE) | ASTM D412-9 | >295 psi |

0420/EDPADS

Please refer to our website at www.tremcosealants.com for the most up-to-date Data Sheet.