



Enviro-Dri® Brick Ledge

Cold-applied, self-adhering membrane

DATA SHEET

Product Description

Enviro-Dri Brick Ledge is a cold-applied, self-adhering membrane composed of triple woven polypropylene on one side and a layer of butyl-modified asphalt on the other. This product fully integrates with the Enviro-Dri Weather-Resistant Barrier System to provide you with the next level of protection against air and moisture intrusion. This product can also be used with our standard below-grade waterproofing products and systems to protect the brick ledge from moisture intrusion.

Basic Uses

Seals brick ledge from moisture intrusion. Can be used with Enviro-Dri Weather-Resistant Barrier Systems and Tremco's waterproofing products.

Features & Benefits

- Fully adhered system
- Seals around brick ledge
- Forms a positive air/vapor barrier
- 6-month UV exposure rating
- Excellent overlap adhesion

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TYPICAL MEMBRANE PROPERTIES

PROPERTY	DESCRIPTION	
COLOR	Black	
THICKNESS	40 mils	
PACKAGING	Roll Width: 12" (3 rolls / carton) 18" (2 rolls / carton)	Roll Length: 66'
APPLICATION	Apply at temperatures 20°F or higher	
STORAGE	Store in an unopened container at between 50-90°F	
PROPERTY	TEST METHOD	TYPICAL RESULTS
TENSILE STRENGTH	ASTM D412	>1600 psi
ELONGATION (ADHESIVE ONLY)	ASTM D412	500%
PERMEANCE	ASTM E96	<0.5
LOW TEMPERATURE FLEX	ASTM D1970	No cracks or delamination
NAIL SEALABILITY	ASTM D1970	Pass

0420/EDBLDS

Please refer to our website at www.tremcosealants.com for the most up-to-date Data Sheet.

Tremco Construction Products Group

3735 Green Rd
Beachwood OH 44122
800.876.5624

1451 Jacobson Ave
Ashland OH 44805
419.289.2050 / 800.321.6357

220 Wicksteed Ave
Toronto ON M4H1G7
416.421.3300 / 800.363.3213

1445 Rue de Coulomb
Boucherville QC J4B 7L8
514.521.9555