

SIMPLE SEAL SOLUTIONS

The simple, long-lasting solution for leak-free buildings.

Technologies

Simple Seal high-performance extrusions are designed to seal joints and gaps ranging from low to high movement conditions. For new construction and restoration projects, Simple Seal provides flexible, tear-resistant properties that will help to protect your building from air and moisture penetration.

Whether the need is for over an existing coating or under a new protective coating, Simple Seal offers a solution for that's right for your project.

Typical applications include window and door perimeters, Dryvit®/EIFS joints, parapet walls, skylights, aluminum window seals, transition seals, curtain wall metal-to-metal joinery, sheet metal roof joints, penetrations, and many other gap and joint conditions.

Features & Benefits

- Ease of installation reduces time and labor costs.
- Superior flexibility and movement capability.
- Excellent tear resistance.
- Wide operational temperature range.
- Non-corrosive and corrosion resistant.
- Available in a range of widths.
- Custom designs with one or more notches.



	Technology	Printable	Left Exposed	Expansion Joints	Tear Resistance	Custom Notched	Door/Window Perimeter	Metal Joinery	Internal Glazing Seals	Under Coatings & Membranes	Warranty
Spectrem® Simple Seal Extruded Silicone Bridge)	Silicone	•	•	•	•	•	•	•	•	•	20 yr with Spec 1
Dymonic® Simple Seal Extruded Polyurethane Bridge		•	0-6	•	•	•	•			•	10 yr with Dym 100

Spectrem® Simple Seal

STANDARD STOCK SIZES: 1", 1.5", 2", 3", 4", 6" (25, 38, 51, 76, 152 mm) [highlighted in chart below]

STANDARD STOCK COLORS: Black, White, Anodized Aluminum, Bronze, Aluminum Stone, Limestone, Sandstone [highlighted in chart below]

SPECIAL SIZES: Other sizes available include 2-1/2" (64 mm), 5" (127 mm) and 7 to 14" (178 to 355 mm) in 1" (25 mm) increments

SPECIAL COLORS: Adobe Tan, Buff, Champagne, Dark Bronze, Dusty Rose, Gray, Ivory, Light Bronze, Off White, Precast White, Rustic Brick

Width in Inches (Millimeters)	Stock Size	Lead Time	Min. Quantity Order in Feet (Meters)	Selling Unit of Measure	Feet (Meters) / Case
1" (25)	Yes	4 Days	100' (30.5)	1 Roll	100' (30.5)
1.5" (38)	Yes	4 Days	100' (30.5)	1 Roll	100' (30.5)
2" (51)	Yes	4 Days	100' (30.5)	1 Roll	100' (30.5)
2.5" (64)	No	3 Weeks	500' (152.4)	1 Roll	100' (30.5)
3" (76)	Yes	4 Days	100' (30.5)	1 Roll	100' (30.5)
4" (102)	Yes	4 Days	100' (30.5)	1 Roll	100' (30.5)
5" (127)	No	3 Weeks	500' (152.4)	1 Roll	100' (30.5)
6" (152)	Yes	4 Days	100' (30.5)	1 Roll	100' (30.5)
7" (178)	No	3 Weeks	500' (152.4)	1 Roll	100' (30.5)
8" (203)	No	3 Weeks	500' (152.4)	1 Roll	100' (30.5)
9" (229)	No	3 Weeks	500' (152.4)	1 Roll	100' (30.5)
10" (254)	No	3 Weeks	250' (76.2)	1 Roll	50 (15.2)
11" (279)	No	3 Weeks	250' (76.2)	1 Roll	50 (15.2)
12" (305)	No	3 Weeks	250' (76.2)	1 Roll	50 (15.2)
13" (330)	No	3 Weeks	250' (76.2)	1 Roll	50 (15.2)
14" (355)	No	3 Weeks	250' (76.2)	1 Roll	50 (15.2)



Dymonic® Simple Seal

STANDARD STOCK SIZES: 1.5", 2", 3", 4", 6"
(38, 51, 76, 152 mm)

STANDARD STOCK COLORS: Light Gray

SPECIAL SIZES: 1", 2.5", 3.5", 4.5", 5", and 5.5"
(25, 63.5, 88.9, 114.3, 127, and 139.7)



Width in Inches (Millimeters)	Stock Size	Lead Time	Mini Quantity Order in Feet (Meters)	Selling Unit of Measure	Feet (Meters)/Case
1" [25]	No	3 Weeks	500' (152.4)	1 Roll	100' (30.5)
1.5" [38]	Yes	4 Days	100' (30.5)	1 Roll	100' (30.5)
2" [51]	Yes	4 Days	100' (30.5)	1 Roll	100' (30.5)
2.5" [64]	No	3 Weeks	500' (152.4)	1 Roll	100' (30.5)
3" [76]	Yes	4 Days	100' (30.5)	1 Roll	100' (30.5)
3.5" [89]	No	3 Weeks	500' (152.4)	1 Roll	100' (30.5)
4" [102]	Yes	4 Days	100' (30.5)	1 Roll	100' (30.5)
4.5" [114]	No	3 Weeks	500' (152.4)	1 Roll	100' (30.5)
5" [127]	No	3 Weeks	500' (152.4)	1 Roll	100' (30.5)
5.5" [140]	No	3 Weeks	500' (152.4)	1 Roll	100' (30.5)

Tremco Commercial Sealants & Waterproofing | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together Tremco Incorporated's Commercial Sealants & Waterproofing and Roofing & Building Maintenance operating divisions; Dryvit Systems, Inc.; Nudura Inc.; Willseal; Weatherproofing Technologies, Inc. and Weatherproofing Technologies Canada, Inc.



Tremco®, Spectrem®, and Dymonic® are registered trademarks of Tremco Incorporated. Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.

0221/SSOL

tremcocpg.com