



TECHNICAL DATA SHEET

TREMCO®2011 REINFORCING FABRIC

Reemay Reinforcing Fabric 2011

PRODUCT DESCRIPTION

A spun-bonded polyester fabric style 2011, consisting of a nonwoven fabric of continuous filament polyester fibers that are randomly arranged. These fibers are highly dispersed and bonded at the filament junctions.

BASIC USES

Tremco® Reinforcing Fabric is used to reinforce hot fluid-applied membranes in mutli-lift applications.

AVAILABILITY

Immediately available from your local Tremco Sales Representative or Tremco Distributor. For distributor locations, visit www.tremcosealants.com.

PACKAGING

84" x 675' (2.13 M x 205.74 M) roll

36" x 600' (0.91 M x 183 M) roll

12" x 600' (30 cm x 183 M) roll

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUES
Color		White
Weight	ASTM D3776	0.75 oz/yd ² (25 gsm)
Thickness (mil)	ASTM D1777	8.0 mil (0.20 mm)
Sheet Grab Tensile (lb - MD x XD)	ASTM D4632	15.4 lbs x 11.2 lbx (69 N x 50 N)
Trapezoid Tear (lb - MD x XD)	ASTM D1117	4.9 lbs x 5.8 lbx (21.8 N x 25.8 N)

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

REEMAYDS/0523

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com