



TECHNICAL DATA SHEET

Tremco® 2014
Reinforcing Fabric
Reemay Reinforcing Fabric 2014

PRODUCT DESCRIPTION

A spun-bonded polyester fabric consisting of a nonwoven fabric of continuous filament polyester fibers that are randomly arranged. These fibers are highly dispersed and thermally bonded at the filament junction.

BASIC USES

Tremco® Reinforcing Fabric is used to reinforce fluid-applied membranes in multi-lift applications.

AVAILABILITY

Immediately available from your local Tremco Sales Representative or Tremco Distributor. For distributor locations, visit www.tremcosealants.com.

PACKAGING

84" x 675' (2.13 M x 206 M) roll
36" x 600' (0.91 M x 183 M) roll
12" x 600' (30 cm x 183 M) roll
6" x 600' (15 cm x 183 M) roll

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUES
Color		White
Weight		1.0 oz/yd ²
Thickness (Mil)		9 mil
Sheet Grab Tensile (lb - MD x XD)	ASTM D2553	21 lb x 17 lb
Trapezoid Tear (lb - MD x XD)	ASTM D2263	6 lb x 11 lb
Mullen Burst (psi)	ASTM D2553	22 psi

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

REEMAYDS/1122

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com